



The PROCTER Diamond Top Bollard

The PROCTER Diamond Top Bollard is a square, galvanised mild steel bollard with a pressed steel, fully welded cap. The Diamond Top Bollard is an elegantly simple bollard, ideal for providing protection against unauthorised parking or access. The Diamond Top Bollard is ideal for use around pedestrian precincts, pavements, play and parking areas, as part of traffic calming measures, pedestrianisation schemes and as a deterrent to ram-raiders. The Diamond Top Bollard is available in galvanised and galvanised & coated finishes. It is also available Ragged for casting in to concrete or Flanged for bolting down.

The PROCTER Diamond Top Bollard is shown with optional red and white coated finish.

Product Range

Order Code	Description	Weight
138 121 900	100mm x 100mm (Ragged)	12.0kg
138 121 901	100mm x 100mm (Flanged)	12.0kg
138 121 905	150mm x 150mm (Ragged)	31.0kg
138 121 910	150mm x 150mm (Flanged)	31.0kg

Product details

1,000mm Tall.

Ragged Posts 400mm below ground.

100mm x 100mm 3mm wall thickness mild steel.

150mm x 150mm 5mm wall thickness mild steel.

Galvanised steel finish.

Installation & use

Flanged bollards require bolting down to a suitable concrete surface (no less than 300mm cube) by means of three M12 bolts.

Ragged bollards require a hole of at least 500mm deep for casting into concrete.

Ragged bollards are supplied with welded fixing spikes to ensure firm ground anchorage.

This product is guaranteed for 12 months (*if installed and used correctly*).

Tel Sales : 02920 855756 - Fax : 02920 887005 - Email : Enquiries@ProcterContracts.co.uk

Procter Contracts - North
 Isabella Road
 Leeds
 LS25 2DY

Procter Contracts - South West
 11 Pantglas Industrial Estate
 Bedwas
 CF83 8XD

Procter Contracts -South East
 Codham Hall
 Brentwood
 CM13 3JT