



PROCTER Galvanised Seats & Benches

With its simple design, the Galvanised Seats & Benches are ideal for busy public areas. The bench and the seat have both been designed to withstand the toughest conditions and to look good for years with only minimal maintenance.

Manufactured in the UK, both the Bench and Seat are available in galvanised mild steel or grade 304 stainless steel. All galvanised products can be coated in any BS or RAL colour (codes must be specified at time of order). Available ragged and flanged

r roduct range				
	Order Code	Description	Weight	
	138 117 031	Galvanised Seat*	96.0kg	
	138 117 036	Stainless Seat	80.0kg	
	138 117 034	Galvanised Bench*	90.0kg	

Product details

Product Pance

138 117 039

- Galvanised Seat: 817mm x 600mm x 1963mm (h x w x l)
- Galvanised Bench: 680mm x 473mm x 1963mm (h x w x l)

Stainless Bench

- Seat height: 500mm
- 400mm below ground (ragged only)

Installation & use

74.0kg

Supplied fully welded for easy installation on site. Ragged versions require a hole of 400mm³ for each leg for casting into concrete. Flanged versions require bolting to established concrete of at least 400mm³ per leg by means of four 12mm bolts. These products are guaranteed for 12 months (if installed and used correctly).

Tel Sales: 02920 855756 Fax: 02920 887005 Email: Enquiries@procterContracts.co.uk

^{*} Coated variant available on request (BS/RAL colours must be specified at time of order).





PROCTER Galvanised Bench

Product Range

Order Code	Description	Weight
138 117 014	Galvanised Bench (mild steel)*	55.0kg
138 117 019	Bench (Stainless Steel)	53.0kg

^{*} Coated variant available (please specify BS/ RAL numbers at time of order)

Product details

- 500mm x 594mm x 1760mm (h x w x l)
- 40mm x 5mm slats

Installation & use

Supplied fully welded for easy installation on site. The galvanised bench requires a trench of a least 1000mm x 600mm x 300mm deep for casting into concrete. Clean off any concrete splashes after installation. Always allow sufficient time for concrete to cure before usage. This product is guaranteed for 12 months (if installed and used correctly)

Tel Sales: 02920 855756 - Fax: 02920 887005 - Email: Enquiries@procterContracts.co.uk