



The PROCTER Height Restrictor (Swing with Swing Gate)

The PROCTER Height Restrictor (Swing with Swing Gate) are for use where a height restriction is necessary to prevent access to high sided vehicles, with the combined benefit of closing off access for the entire site when required. This combination product of PROCTER's Swing Height Restrictor and Swing Gate is ideal for ensuring control of site access.

The standard clearance of the Height Restrictor is 2.05m (+/- 70mm). The steel is galvanised to ensure longevity and painted red (other colours available, on request). The knocking bar (where fitted) is 48mm diameter tube, painted white with red reflective bands. The Swing Gate is manufactured from 60mm mild steel square tube and is designed to be self-latching with the leading edge of the gate low enough to ensure the gate is as safe as possible.

The Height Restrictor (Swing with Swing Gate) is available with a range of options including Ragged (for casting in to new concrete) and Flanged feet (for bolting to existing concrete), with or without knocking bar and galvanised only.

Product Range

| Order Code | Description |
|-------------|--|
| 138 106 636 | 3.0m Height Restrictor Swing with Swing Gate - Flanged, including knocking bar (Galvanised & Coated) |
| 138 106 646 | 4.0m Height Restrictor Swing with Swing Gate - Flanged, including knocking bar (Galvanised & Coated) |
| 138 106 656 | 5.0m Height Restrictor Swing with Swing Gate - Flanged, including knocking bar (Galvanised & Coated) |
| 138 106 666 | 6.0m Height Restrictor Swing with Swing Gate - Flanged, including knocking bar (Galvanised & Coated) |
| 138 106 676 | 7.0m Height Restrictor Swing with Swing Gate - Flanged, including knocking bar (Galvanised & Coated) |

(All sizes are measured between the inner edges of the Flanges)
Please refer to the Price List for the full range.

Accessories & installation parts

| | |
|-------------|--|
| 138 106 287 | 'MAX. HEIGHT 2.05 METRES' Warning Sign |
| 138 106 669 | Catch Post for Height Restrictor Swing with Swing Gate (Ragged, Galvanised & Coated) |
| 138 100 990 | M16 Foundation Bolt (4 required per barrier) |

Product details

Standard Clearance; 2.05m (+/- 70mm)

Base Plate; 400mm x 400mm x 10mm.

Main Tube; 120mm x 120mm.

Galvanised steel, painted Red.

48mm knocking bar, coated white with Red Reflective Tape.

Installation & use

Height Restrictor (Fixed) requires bolting down to a suitable concrete surface (not less than 600mm cubed) by means of four 16mm anchor bolts (Flanged). It is recommended that suitable signs are placed to ensure vehicles are aware of the obstruction.

This product is guaranteed for 12 months (*if installed and used correctly*).

Tel Sales : 02920 855756 - Fax : 02920 887005 - Email : Enquiries@procterContracts.co.uk