

DESIGN . SUPPLY * INSTALL





The PROCTER PAX1 Cycle Shelter

The PAX1 Cycle Shelter is a 'lean-to' bicycle shelter, designed to be fixed against a suitable wall. The PAX Shelter is a budget shelter which can trace it's roots back to the 1950's. This simple, functional shelter is constructed of a tubular steel frame with corrugated roof panels. The Shelter can be extended by the addition of extension bays, the shelter is available with Ragged feet for casting into existing concrete or with Flanged feet, for bolting to an existing suitable concrete surface. Side Cladding Panels are also available to offer greater protection from the elements.

The PAX1 Cycle Shelter can accomodate up to 10 bicycles with a Type B Cycle Rack (Shown with 3 no. SU(V) Cycle Stands).

Options

Order Code	Description	Weight
138 200 008	Main Bay (Ragged)	120.0kg
138 200 010	Main Bay (Flanged)	120.0kg
138 200 009	Extension Bay (Ragged)	100.0kg
138 200 011	Extension Bay (Flanged)	100.0kg

Accessories & installation parts

138 200 041	PAX1 Side Cladding
138 200 041	PAX1 Side Cladding (Plastisol)

Product details

2,175mm (Height, Front). 2,480mm (Height, Rear). 2,440mm (Depth). 3,355mm (Length). 48mm galvanised steel tube. Corrugated Galvanised Roof Sheet. Other options are available; please ask.

Installation & use

Each shelter leg requires bolting down to a suitable concrete surface (not less than 300mm x 300mm x 300mm) by means of 3 no. 12mm anchor bolts. The wall support requires fixing to a suitable, sound wall by means of 2 no. 12mm anchor bolts per flange. The area surrounding the installation must be flat and level with no nearby surface irregularities or gradient changes. On-site assembly requires construction skill.

This product is guaranteed for 12 months (if installed and used correctly).

Tel Sales: 02920 855756 Fax: 02920 887005 Email: Enquiries@ProcterContracts.co.uk



DESIGN • SUPPLY * INSTALL





The PROCTER PAX2 Cycle Shelter

The PAX2 Cycle Shelter is a free-standing bicycle shelter, with a roof sloping from the back to the front. The PAX Shelter is a budget shelter which can trace it's roots back to the 1950's. This simple, functional shelter is constructed of a tubular steel frame with corrugated roof panels. The Shelter can be extended by the addition of extension bays, the shelter is available with Ragged feet for casting into existing concrete or with Flanged feet, for bolting to an existing suitable concrete surface. Side Cladding Panels are also available to offer greater protection from the elements.

The PAX2 Cycle Shelter can accomodate up to 10 bicycles with a Cycle Rack. The Shelters shown include the optional side and rear cladding and are shown with Cycle Racks.

Options

Order Code

Oraci Ooac	Bescription	Weight
138 200 014	Main Bay (Ragged)	140.0kg
138 200 012	Main Bay (Flanged)	140.0kg
138 200 009	Extension Bay (Ragged)	110.0kg
138 200 011	Extension Bay (Flanged)	110.0kg
	Accessories & installation parts	
138 200 042	PAX2/3 Side Cladding (Clear PVC)	

138 200 043 PAX2 Side Cladding 138 200 045 PAX2 Rear Cladding 138 200 065 PAX2/3 Guttering Pack

Description

Product details

Waight

2,175mm (Height, Front). 2,480mm (Height, Rear). 2,440mm (Depth). 3,355mm (Length). 48mm galvanised steel tube. Corrugated Galvanised Roof Sheet. Other options are available; please ask.

Installation & use

Each shelter leg requires bolting down to a suitable concrete surface (not less than 300mm x 300mm x 300mm) by means of 3 no. 12mm anchor bolts. The area surrounding the installation must be flat and level with no nearby surface irregularities or gradient changes. On-site assembly requires construction skill.

This product is guaranteed for 12 months (if installed and used correctly).

Tel Sales: 02920 855756 Fax: 02920 887005 Email: Enquiries@procterContracts.co.uk



The PROCTER PAX3 Cycle Shelter

Description

138 200 046 PAX3 Rear Cladding 138 200 065 PAX2/3 Guttering Pack

The PAX3 Cycle Shelter is a free-standing bicycle shelter, with a roof sloping from the front to the back. The PAX Shelter is a budget shelter which can trace it's roots back to the 1950's. This simple, functional shelter is constructed of a tubular steel frame with corrugated roof panels. The Shelter can be extended by the addition of extension bays, the shelter is available with Ragged feet for casting into existing concrete or with Flanged feet, for bolting to an existing suitable concrete surface. Side Cladding Panels, Rear Cladding and Lockable Doors are all available as options to offer greater protection from the elements.

The PAX2 Cycle Shelter can accomodate up to 10 bicycles with a Cycle Rack. The Shelter shown includes the optional Lockable Doors, Guttering Pack and Side and Rear cladding.

Options

Order Code

C. ac. Coac	2000.15.10.11	
138 200 018	Main Bay (Ragged)	140.0kg
138 200 016	Main Bay (Flanged)	140.0kg
138 200 019	Extension Bay (Ragged)	110.0kg
138 200 017	Extension Bay (Flanged)	110.0kg
	Accessories & installation parts	
138 200 042	PAX2/3 Side Cladding (Clear PVC)	
138 200 053	PAX3 Side Cladding	

Product details

Weight

2,404mm (Height, Front). 2,210mm (Height, Rear).
2,440mm (Depth).
3,355mm (Length).
48mm galvanised steel tube.
Corrugated Galvanised Roof Sheet.
Other options are available; please ask.

Installation & use

Each shelter leg requires bolting down to a suitable concrete surface (not less than 300mm x 300mm x 300mm) by means of 3 no. 12mm anchor bolts.

The area surrounding the installation must be flat and level with no nearby surface irregularities or gradient changes.

On-site assembly requires construction skill.

This product is guaranteed for 12 months (if installed and used correctly).

Tel Sales: 02920 855756 - Fax: 02920 887005 - Email: Enquiries@procterContracts.co.uk



DESIGN . SUPPLY . INSTALL





The PROCTER PAX4 Cycle Shelter

The PAX4 Cycle Shelter is a free-standing double sided bicycle shelter, suitable for two rows of cycle parking. The PAX Shelter is a budget shelter which can trace it's roots back to the 1950's. This simple, functional shelter is constructed of a tubular steel frame with corrugated roof panels. The Shelter can be extended by the addition of extension bays, the shelter is available with Ragged feet for casting into existing concrete or with Flanged feet, for bolting to an existing suitable concrete surface. Side Cladding Panels are available as an option to offer greater protection from the elements.

The PAX4 Cycle Shelter can accomodate up to 20 bicycles with a Cycle Rack. The Shelter shown is a Main Bay with an Extension Bay and can accomodate up to 40 bicycles.

Options

Order Code	Description	Weight
138 200 020	Main Bay (Ragged)	250.0kg
138 200 022	Main Bay (Flanged)	250.0kg
138 200 021	Extension Bay (Ragged)	220.0kg
138 200 023	Extension Bay (Flanged)	220.0kg

Accessories & installation parts

138 200 044 PAX4 Side Cladding

Product details

2,390 (Height, Apex). 2,175mm (Height, Front & Rear).
4,880mm (Depth).
3,355mm (Length).
48mm galvanised steel tube.
Corrugated Galvanised Roof Sheet.
Other options are available; please ask.

Installation & use

Each shelter leg requires bolting down to a suitable concrete surface (not less than 300mm x 300mm x 300mm) by means of 3 no. 12mm anchor bolts.

The area surrounding the installation must be flat and level with no nearby surface irregularities or gradient changes.

On-site assembly requires construction skill.

This product is guaranteed for 12 months (if installed and used correctly).

Tel Sales: 02920 855756 - Fax: 02920 887005 - Email: Enquiries@procterContracts.co.uk