



The PROCTER Parking Post

The parking post is the padlockable variant of the original hinged parking post; patented in 1959, and still the preferred choice for the protection of individual parking spaces throughout Britain.

The extremely durable and reliable design of the parking post ensures your parking space will always be available. The reflective, high visibility band ensures your parking post will always be seen.

The PROCTER parking post is locked by fitting a padlock to the top of the post through the lower hole of the bar protruding through the cap, the padlock can also be fitted in the upper hole, thus allowing the post to be raised or lowered.

The PROCTER parking post is also available in stainless steel.

Product Range

Order Code	Description	Weight
138300301	Parking Posts (Galvanised)	8.0kg
138300304	Parking Posts (Galvanised & Coated Yellow)	8.0kg

Accessories & installation parts

138100906	40mm Brass Padlock with 2 keys (Random Key)
138100907	40mm Brass Padlock with 2 keys (Identical Key)
138100991	M16 Expanding Bolt (2 required per post)
138100990	M16 Foundation Bolt (2 required per post)
138100992	M16 Rawl Bolt (2 required per post)

Product details

750mm x 203mm x 102mm (h x w x l).
64mm outside diameter galvanised steel tube body.
Polyurethane cap.
110mm minimum vehicle clearance.

Installation & use

Each post requires bolting down to a suitable concrete surface (not less than 300mm cubed) by means of two 16mm anchor bolts. The area surrounding the installation must be flat and level with no nearby surface irregularities or gradient changes. Care must be taken to ensure the circular base recess is kept clear of cement and any other debris during installation and use. This product is guaranteed for 12 months (*if installed and used correctly*).

Tel Sales : 02900 855756 - Fax : 02920 887005 - Email : info@procterstreetfurniture.co.uk

Procter Contracts - North
Isabella Road
Leeds
LS25 2DY

Procter Contracts - South West
11 Pantglas Industrial Estate
Bedwas
CF83 8XD

Procter Contracts -South East
Codham Hall
Brentwood
CM13 3JT



The PROCTER Sprung Boundary Post

Designed for use delineating the edge of car parking spaces, the Sprung Boundary Post has a spring incorporated into the base which allows it to absorb low speed impacts and return to it's original upright position.

The post can deflect up to 30° from the vertical. The Sprung Boundary Post is available in Galvanised and Galvanised and Coated finishes, and is further available either ragged for casting in to concrete or flanged for bolting down.

The reflective, high visibility band ensures your parking post will always be seen.

Product Range

Order Code	Description	Weight
138100403	Flanged	3.5kg
138100503	Ragged	3.5kg
138100405	Flanged (Coated Yellow)	3.5kg
138100505	Ragged (Coated Yellow)	3.5kg

Accessories & installation parts

138100994	M12 Expanding Bolt
138100993	M12 Foundation Bolt
138100995	M12 Rawl Bolt

Product details

750mm (above ground).
48mm outside diameter galvanised steel tube body.
134mm diameter flange.
Polyurethane cap.

Installation & use

Each flanged post requires bolting down to a suitable concrete surface (not less than 300mm cubed) by means of three 12mm anchor bolts.
Each ragged post requires casting into concrete (not less than 300mm cubed).
This product is guaranteed for 12 months (*if installed and used correctly*).

Tel Sales : 02920 855756 - Fax : 02920 887005 - Email : Enquiries@procterContracts.co.uk



The PROCTER Stealth Parking Post

The original hinged parking post; patented in 1959 is still the preferred choice for the protection of individual parking spaces throughout Britain, the Stealth Post has all the benefits of the original but with the further advantage of a fully flush to ground level socket.

The extremely durable and reliable design of the parking post ensures your parking space will always be available. The reflective, high visibility band ensures your parking post will always be seen.

The PROCTER parking post is push-down to lock and is unlocked by pressing down on the cap and rotating the key (Supplied with 2 keys). The post is then fully raised or lowered and relocked.

The PROCTER Stealth parking post is also available in stainless steel.

Product Range

Order Code	Description	Weight
138 300 401	Random Key	18.0kg
138 300 404	Random Key (Coated; Please specify BS/RAL colour)	18.0kg
138 300 405	Random Key Coated; Yellow)	18.0kg
138 300 406	Random Key (Coated; Black)	18.0kg
138 300 409	Random Key (Grade 304 Stainless)	18.0kg
138 300 450	Identical Key	18.0kg
138 300 454	Identical Key (Coated; Please specify BS/RAL colour)	18.0kg
138 300 455	Identical Key Coated; Yellow)	18.0kg
138 300 456	Identical Key (Coated; Black)	18.0kg
138 300 459	Identical Key (Grade 304 Stainless)	18.0kg

Accessories & installation parts

138 150 501 Spare Key (Please specify key number)

Product details

660mm above ground (post raised)
835mm x 220mm x 95mm (Socket; Length x Width x Depth).
64mm outside diameter galvanised steel tube body.
Polyurethane cap.

Installation & use

It is recommended that posts are placed no further than 1,200mm apart to ensure no vehicle may pass between the raised posts.
An excavated hole of approximately 100mm deep, 1,200mm long and 400mm wide is required for installation.
The area surrounding the installation must be flat and level with no nearby surface irregularities or gradient changes.
Care must be taken to ensure the circular base recess is kept clear of cement and any other debris during installation and use.
This product is guaranteed for 12 months (*if installed and used correctly*).

Tel Sales : 02920 855756 - Fax : 02920 887005 - Email : Enquiries@procterContracts.co.uk



The PROCTER Stealth Parking Post

The original hinged parking post; patented in 1959 is still the preferred choice for the protection of individual parking spaces throughout Britain, the Stealth Post has all the benefits of the original but with the further advantage of a fully flush to ground level socket.

The extremely durable and reliable design of the parking post ensures your parking space will always be available. The reflective, high visibility band ensures your parking post will always be seen.

The PROCTER parking post is push-down to lock and is unlocked by pressing down on the cap and rotating the key (Supplied with 2 keys). The post is then fully raised or lowered and relocked.

The PROCTER Stealth parking post is also available in stainless steel.

Product Range

Order Code	Description	Weight
138 300 440	Master Suited Key	18.0kg
138 300 444	Master Suited Key (Coated; Please specify BS/RAL colour)	18.0kg
138 300 445	Master Suited Key Coated; Yellow)	18.0kg
138 300 446	Master Suited Key (Coated; Black)	18.0kg
138 300 449	Master Suited Key (Grade 304 Stainless)	18.0kg

Accessories & installation parts

138 100 210	Master Key (For Master suited posts only)
-------------	---

Product details

660mm above ground (post raised)
835mm x 220mm x 95mm (Socket; Length x Width x Depth).
64mm outside diameter galvanised steel tube body.
Polyurethane cap.

Installation & use

It is recommended that posts are placed no further than 1,200mm apart to ensure no vehicle may pass between the raised posts.

An excavated hole of approximately 100mm deep, 1,200mm long and 400mm wide is required for installation.

The area surrounding the installation must be flat and level with no nearby surface irregularities or gradient changes.

Care must be taken to ensure the circular base recess is kept clear of cement and any other debris during installation and use.

This product is guaranteed for 12 months (*if installed and used correctly*).

Tel Sales : 02920 855756 - Fax : 02920 887005 - Email : Enquiries@procterContracts.co.uk



The PROCTER Hinged Parking Post

The original hinged parking post; patented in 1959, and still the preferred choice for the protection of individual parking spaces throughout Britain.

The extremely durable and reliable design of the parking post ensures your parking space will always be available. The reflective, high visibility band ensures your parking post will always be seen.

The PROCTER parking post is push-down to lock and is unlocked by pressing down on the cap and rotating the key (Supplied with 2 keys). The post is then fully raised or lowered and re-locked.

The PROCTER Hinged parking post is also available in stainless steel.

Product Range

Order Code	Description	Weight
138 300 001	Galvanised	8.0kg
138 300 004	Galvanised (Coated; please specify BS/ RAL colour at time of order)	8.0kg
138 300 005	Galvanised (Coated yellow)	8.0kg
138 300 006	Galvanised (Coated black)	8.0kg
138 300 009	Stainless Steel (Grade 304)	8.0kg

Accessories & installation parts

138 150 501	Spare Key (Please specify key number)
138 100 991	M16 Expanding Bolt (2 required per post)
138 100 990	M16 Foundation Bolt (2 required per post)
138 100 992	M16 Rawl Bolt (2 required per post)

Product details

750mm x 203mm x 102mm (h x w x l).
64mm outside diameter galvanised steel tube body.
Polyurethane cap.
110mm minimum vehicle clearance.

Installation & use

Each post requires bolting down to a suitable concrete surface (not less than 300mm cubed) by means of two 16mm anchor bolts. The area surrounding the installation must be flat and level with no nearby surface irregularities or gradient changes. Care must be taken to ensure the circular base recess is kept clear of cement and any other debris during installation and use. This product is guaranteed for 12 months (*if installed and used correctly*).

Tel Sales : 02920 855756 - Fax : 02920 887005 - Email : Enquiries@procterContracts.co.uk



The PROCTER Hinged Parking Post

The original hinged parking post; patented in 1959, and still the preferred choice for the protection of individual parking spaces throughout Britain.

The extremely durable and reliable design of the parking post ensures your parking space will always be available. The reflective, high visibility band ensures your parking post will always be seen.

The PROCTER parking post is push-down to lock and is unlocked by pressing down on the cap and rotating the key (Supplied with 2 keys). The post is then fully raised or lowered and re-locked.

The PROCTER Hinged parking post is also available in stainless steel.

Product Range

Order Code	Description	Weight
138 300 101	Galvanised	8.0kg
138 300 104	Galvanised (Coated; please specify BS/ RAL colour at time of order)	8.0kg
138 300 105	Galvanised (Coated yellow)	8.0kg
138 300 106	Galvanised (Coated black)	8.0kg
138 300 109	Stainless Steel (Grade 304)	8.0kg

Accessories & installation parts

138 150 501	Spare Key (Please specify key number)
138 100 991	M16 Expanding Bolt (2 required per post)
138 100 990	M16 Foundation Bolt (2 required per post)
138 100 992	M16 Rawl Bolt (2 required per post)

Product details

750mm x 203mm x 102mm (h x w x l).
64mm outside diameter galvanised steel tube body.
Polyurethane cap.
110mm minimum vehicle clearance.

Installation & use

Each post requires bolting down to a suitable concrete surface (not less than 300mm cubed) by means of two 16mm anchor bolts. The area surrounding the installation must be flat and level with no nearby surface irregularities or gradient changes. Care must be taken to ensure the circular base recess is kept clear of cement and any other debris during installation and use. This product is guaranteed for 12 months (*if installed and used correctly*).

Tel Sales : 02920 855756 - Fax : 02920 887005 - Email : Enquiries@procterContracts.co.uk



The PROCTER Hinged Parking Post

The original hinged parking post; patented in 1959, and still the preferred choice for the protection of individual parking spaces throughout Britain.

The extremely durable and reliable design of the parking post ensures your parking space will always be available. The reflective, high visibility band ensures your parking post will always be seen.

The PROCTER parking post is push-down to lock and is unlocked by pressing down on the cap and rotating the key (Supplied with 2 keys). The post is then fully raised or lowered and re-locked.

The PROCTER Hinged parking post is also available in stainless steel.

Product Range

Order Code	Description	Weight
138 300 201	Galvanised	8.0kg
138 300 211	Galvanised (Coated; please specify BS/ RAL colour at time of order)	8.0kg
138 300 205	Galvanised (Coated yellow)	8.0kg
138 200 206	Galvanised (Coated black)	8.0kg

Accessories & installation parts

138 150 501	Spare Key (Please specify key number)
138 100 201	Master Key (For Master Suited locks only)
138 100 991	M16 Expanding Bolt (2 required per post)
138 100 990	M16 Foundation Bolt (2 required per post)
138 100 992	M16 Rawl Bolt (2 required per post)

Product details

750mm x 203mm x 102mm (h x w x l).
64mm outside diameter galvanised steel tube body.
Polyurethane cap.
110mm minimum vehicle clearance.

Installation & use

Each post requires bolting down to a suitable concrete surface (not less than 300mm cubed) by means of two 16mm anchor bolts. The area surrounding the installation must be flat and level with no nearby surface irregularities or gradient changes. Care must be taken to ensure the circular base recess is kept clear of cement and any other debris during installation and use. This product is guaranteed for 12 months (*if installed and used correctly*).

Tel Sales : 02920 855756 - Fax : 02920 887005 - Email : Enquiries@procterContracts.co.uk