



The PROCTER Removable Bollard 1000 (Galvanised)

The Removable Bollard offers an effective, simple and robust way to protect premises and vehicles. Removable Bollards are particularly suitable for locations where occasional access is required, the simple pin and padlock system provides an easy to operate solution for locking the bollard in place. The Removable Bollard is 1,000mm above ground and is available in a range of outside tube diameter sizes from 76mm through to 193mm.

The Removable Bollard 1000 is ideal for protecting vehicle forecourts, commercial premises, car parks and domestic driveways and can be used in conjunction with fixed bollards as part of a security system for all types of premises.

The PROCTER Removable Bollard 1000 is shown in 114mm with the standard galvanised finish.

Product Range

Order Code	Description	Lift Out Weight	Weight
138 121 215	76mm	5.2kg	7.6kg
138 121 280	90mm	6.6kg	9kg
138 121 307	101mm	7.4kg	9.8kg
138 121 408	114mm	8.5kg	10.9kg
138 121 507	127mm	15.3kg	17.7kg
138 121 611	139mm	16.9kg	19.3kg
138 121 677	152mm	18.5kg	20.9kg
138 121 705	168mm	20.5kg	22.9kg
138 121 800	193mm	23.6kg	26kg

Accessories & installation parts

138 501 206	Additional Ground Socket	2.4kg
138 100 906	40mm Brass Padlock with 2 Keys (Random Key)	
138 100 907	40mm Brass Padlock with 2 Keys (Identical Key)	

Product details

1,000mm above ground.
Socket Dimensions 267mm x 152mm x 160mm (h x w x l)
Galvanised Steel Tube Body and Socket.

Installation & use

It is recommended that posts are placed no further than 1,200mm apart to ensure no vehicle may pass between.
The ground socket must be concreted into a hole of approximately 300mm cubed.
The flap should be flush with the surrounding ground level when closed.
Suitable provision for should be allowed for drainage from the bottom of the excavated hole.
This product is guaranteed for 12 months (*if installed and used correctly*).

Tel Sales : 02920 855756 - Fax : 02920 887005 - Email : Enquiries@procterContracts.co.uk



The PROCTER Removable Bollard 1000 (Stainless)

The Removable Bollard offers an effective, simple and robust way to protect premises and vehicles. Removable Bollards are particularly suitable for locations where occasional access is required, the simple pin and padlock system provides an easy to operate solution for locking the bollard in place. The Removable Bollard is 1,000mm above ground and is available in a range of outside tube diameter sizes from 60mm through to 204mm.

The Removable Bollard 1000 is ideal for protecting vehicle forecourts, commercial premises, car parks and domestic driveways and can be used in conjunction with fixed bollards as part of a security system for all types of premises.

The PROCTER Removable Bollard 1000 is shown in 101mm with the standard Stainless Steel Grade 304 finish.

Product Range

Order Code	Description	Lift-out Weight	Weight
138 125 063	60mm	3.1kg	5.5kg
138 125 078	76mm	3.9kg	6.3kg
138 125 088	89mm	4.6kg	7kg
138 125 102	101mm	5.22kg	7.62kg
138 125 115	114mm	5.96kg	8.34kg
138 125 131	129mm	7.24kg	9.64kg
138 125 138	139mm	8.09kg	10.49kg
138 125 170	154mm	8.85kg	11.15kg
138 125 171	168mm	10.8kg	13.2kg
138 125 208	204mm		
Accessories & installation parts			
138 150 206	Additional Ground Socket		2.4kg
138 100 906	40mm Brass Padlock with 2 Key (Random Key)		
138 150 907	40mm Brass Padlock with 2 Keys (Identical Key)		

Product details

1,000mm above ground.
Socket Dimensions 267mm x 152mm x 160mm (hx w x l)
Stainless Steel Grade 304 Tube Body and Socket.

Installation & use

It is recommended that posts are placed no further than 1,200mm apart to ensure no vehicle may pass between.
The ground socket must be concreted into a hole of approximately 300mm cubed.
The flap should be flush with the surrounding ground level when closed.
Suitable provision for should be allowed for drainage from the bottom of the excavated hole.
This product is guaranteed for 12 months (*if installed and used correctly*).

Tel Sales : 02920 855756 - Fax : 02920 887005 - Email : Enquiries@procterContracts.co.uk