



Trolley Bays

Formed from individual Perimeter Barriers, trolley bays can be made to any size in order to suit customer requirements. Configurations can vary depending on the space available. The barriers sit 800mm above the ground and are available with an additional central rail (200mm above the ground) as required.

A more aesthetic alternative to traditional fencing, our barriers can be manufactured from stainless steel or galvanised mild steel. All of our mild steel barriers can be colour coated to any BS or RAL colour (codes must be specified at time of order).

Available ragged and flanged.

Product Range

Order Code	Description	Weight
138 177 690	1,500mm wide Trolley Bay (76mm diameter) Galvanised	
138 177 695	1,900mm wide Trolley Bay (76mm diameter) Galvanised	
138 205 105	1,500mm wide Trolley Bay (48mm diameter) Stainless Steel	

Product details

- Height above ground: 800mm
- Depth below ground: 300mm
- Wall thickness: 3mm

Installation & use

Flanged barriers require bolting down to a suitable concrete surface (no less than 300mm³ per leg).
Ragged versions require setting with concrete into a hole of at least 300mm x 300mm x 450mm (length x width x depth).
Ragged barriers are supplied with welded fixing spikes to ensure firm ground anchorage.
This product is guaranteed for 12 months (if installed and used correctly).

Tel Sales : 02920 855756 - Fax : 02920 887005 - Email : Enquiries@procterContracts.co.uk

Procter Contracts - North
Isabella Road
Leeds
LS25 2DY

Procter Contracts - South West
11 Pantglas Industrial Estate
Bedwas
CF83 8XD

Procter Contracts -South East
Codham Hall
Brentwood
CM13 3JT