



The PROCTER Trolley Protection Rail

Designed with the retail market in mind, the PROCTER Trolley Protection rail is ideal for protecting vulnerable walls and windows from trolley damage. Sitting only 185mm above the ground, this railing can be used to protect both internal and external structures and is commonly found around entrances or glass panels.

Trolley Protection Rails are manufactured to order and overall length must be specified at the time of order.

Product Range

Order Code	Description
138 174 795	1m Galvanised Mild Steel Trolley Protection Rail
138 174 700	1m Stainless Steel Trolley Protection Rail (grade 304)

Product details

- 185mm above ground
- 250mm below ground
- Average leg spacing is 1500mm
- 48mm tube diameter

Installation & use

Ragged railing requires an excavated hole of approximately 300mm cube per leg for installation.
Ragged versions are supplied with welded fixing spikes to ensure firm ground anchorage.
This product is guaranteed for 12 months (if installed and used correctly).

Tel Sales : 02920 855756 - Fax : 02920 887005 - Email : Enquiries@procterContracts.co.uk

Procter Contracts - North
Isabella Road
Leeds
LS25 2DY

Procter Contracts - South West
11 Pantglas Industrial Estate
Bedwas
CF83 8XD

Procter Contracts -South East
Codham Hall
Brentwood
CM13 3JT