



The PROCTER Cycle Stand

The tubular cycle stand, a familiar sight throughout the UK, allows the frame of the bicycle to be secured by the users own security lock. Suitable for securing two bicycles. This is a rolled variant of the ever popular Shef-field cycle stand.

The practical and durable nature of the PROCTER cycle stand ensures it has been consistently recom-mended by cycling groups since it's introduction in the 2000's.

Shown is the galvanised flanged version of the Kirby Cycle Stand.

Options

Order Code	Description	Weight
138515145	Ragged (Galvanised)	10.0kg
138515140	Flanged (Galvanised)	10.0kg
138515147	Ragged (Galvanised & Coated; specify BS/RAL colour)	10.0kg
138515142	Flanged (Galvanised & Coated; specify BS/RAL colour)	10.0kg
138515155	Ragged (Stainless)	10.0kg
138515150	Flanged (Stainless)	10.0kg

Accessories & installation parts

138100994	M12 Expanding Bolt (Flanged only; 6 required per stand)
138100993	M12 Foundation Bolt (Flanged only; 6 required per stand)
138100995	M12 Anchor Bolt (Flanged only; 6 required per stand)

Product details

750mm x 750mm (Length x Height)
48mm outside diameter tube.

Installation & use

Flanged versions require bolting to established concrete of at least 300mm cubed per leg.
Ragged versions require setting with concrete into a hole of at least 300mm x 300mm x 450mm (length x width x depth) per leg.
Allow 800-1,000mm between stands and a minimum of 450mm from any obstruction.
This product is guaranteed for 12 months (*if installed and used correctly*).

Tel Sales : 02920 855756 - Fax : 02920 887005 - Email : Enquiries@procterContracts.co.uk



The PROCTER Cycle Stand

The tubular cycle stand, a familiar sight throughout the UK, allows the frame of the bicycle to be secured by the users own security lock. Suitable for securing two bicycles.

The practical and durable nature of the PROCTER tubular cycle stand ensures it has been consistently favoured by both specifiers and users since it's introduction in the 2000's.

Shown are the galvanised and galvanised & coated flanged versions of the Bilton Cycle Stand.

Options

Order Code	Description	Weight
138515105	Ragged (Galvanised)	11.0kg
138515101	Flanged (Galvanised)	11.0kg
138515110	Ragged (Galvanised & Coated; specify BS/RAL colour)	11.0kg
138515102	Flanged (Galvanised & Coated; specify BS/RAL colour)	11.0kg
138515114	Ragged (Stainless)	11.0kg
138515104	Flanged (Stainless)	11.0kg
Accessories & installation parts		
138100994	12mm Expanding Bolt (Flanged only; 6 required per stand)	

Product details

750mm x 750mm (Length x Height)
48mm outside diameter tube.

Installation & use

Flanged versions require bolting to established concrete of at least 300mm cubed per leg.
Ragged versions require setting with concrete into a hole of at least 300mm x 300mm x 450mm (length x width x depth)
Allow 800-1,000mm between stands and a minimum of 450mm from any obstruction.
This product is guaranteed for 12 months (*if installed and used correctly*).

Tel Sales : 02920 855756 - Fax : 02920 887005 - Email : Enquiries@procterContracts.co.uk

Procter Contracts - North
Isabella Road
Leeds
LS25 2DY

Procter Contracts - South West
11 Pantglas Industrial Estate
Bedwas
CF83 8XD

Procter Contracts -South East
Codham Hall
Brentwood
CM13 3JT