



### **PROCTER Waiting Shelter**

The PROCTER Waiting Shelter is fully enclosed providing a flexible, permanent covering suitable for a wide variety of sites and uses. Full height UV PETG sheeting is used to enclose the strong aluminium frame, protecting occupants from the worst of the weather. With a universal design, this waiting shelter is available up to 6m long, making it ideal for use in both commercial and public areas.

The frame is powder coated grey or black as standard but can be coated in any BS or RAL colour (codes must be specified at time of order). Available flanged only, the PROCTER open spaces Waiting Shelter features an adjustable foot to make installation easier on uneven surfaces.

*PLEASE NOTE: this shelter does not comply with UK & Irish Smoking regulations.*

### **Product Range**

<b>Order Code</b>	<b>Description</b>
138 000 100	2x1m Waiting Shelter
138 000 200	2x2m Waiting Shelter
138 000 230	2x3m Waiting Shelter
138 000 240	2x4m Waiting Shelter
138 000 250	2x5m Waiting Shelter
138 000 260	2x6m Waiting Shelter

#### **Accessories and Installation Parts**

138 000 050	Perch Bench
-------------	-------------

### **Product details**

- Overall Height: 2330mm
- Overall Width: 2050mm
- Foot is adjustable by 70mm on each leg.
- Perch bench: 1900mm x 150mm

### **Installation & use**

Supplied in component form for easy installation.  
Flanged shelters must be bolted down onto a concrete surface (no less than 300mm<sup>3</sup>) per leg by means of one 10mm anchor bolt.  
The area surrounding the installation must be flat and level with no nearby surface irregularities or gradient changes.  
On-site assembly requires construction skill.

This product is guaranteed for 12 months (if installed and used correctly).

**Tel Sales : 02920 855756 - Fax : 02920 887005 - Email : Enquiries@procterContracts.co.uk**