



### **The PGFC 2R Ornamental Mild Steel Bollards**

*The PGFC 2R Ornamental Mild Steel Bollard is suitable for a wide range of locations and purposes. The main post is constructed using mild steel, galvanised to ensure its longevity. Two rings of high grade malleable cast iron are welded onto the steel tube to complete the design.*

*The bollards are available in a galvanised and galvanised and coated finish. RAL numbers must be specified at time of order. Eyelets, hooks and chains can be added to these bollards to complete the decorative effect. Please ask for more information*

### **Product Range**

<b>Order Code</b>	<b>Description</b>	<b>Weight</b>
138 120 151	Ragged	13.0kg
138 120 152	Ragged (Coated Black)	13.0kg
138 120 153	Ragged (Coated; Please specify BS/RAL colour)	13.0kg
138 120 154	Flanged	11.0kg
138 120 155	Flanged (Coated Black)	11.0kg
138 120 156	Flanged (Coated; Please specify BS/RAL colour)	11.0kg

### **Product details**

1000mm above ground  
400mm below ground (ragged only)  
114mm diameter tube  
3mm wall thickness

### **Installation & use**

Flanged bollards require bolting down to a suitable concrete surface (no less than 300mm cube) by means of three M12 bolts.  
Ragged bollards require a hole of at least 400mm deep for casting into concrete.  
Ragged bollards are supplied with welded fixing spikes to ensure firm ground anchorage.  
This product is guaranteed for 12 months (if installed and used correctly).

**Tel Sales : 02920 855756 - Fax : 02920 887005 - Email : [Enquiries@procterContracts.co.uk](mailto:Enquiries@procterContracts.co.uk)**

Procter Contracts - North  
Isabella Road  
Leeds  
LS25 2DY

Procter Contracts - South West  
11 Pantglas Industrial Estate  
Bedwas  
CF83 8XD

Procter Contracts -South East  
Codham Hall  
Brentwood  
CM13 3JT



### **The PROCTER GFC 2R Ornamental Mild Steel Bollards**

The GFC 2R Ornamental Mild Steel Bollard from PROCTER is suitable for a wide range of locations and purposes. The main post is constructed using mild steel, galvanised to ensure its longevity. Two rings of high grade malleable cast iron are welded onto the steel tube to complete the design.

The bollards are available in a galvanised and galvanised and coated finish. RAL numbers must be specified at time of order. Eyelets, hooks and chains can be added to these bollards to complete the decorative effect. Please ask for more information

### **Product Range**

Order Code	Description	Lift out weight	Weight
138 120 157	Removable	13.0kg	18.0kg
138 120 158	Removable (Coated Black)	13.0kg	18.0kg
138 120 159	Removable (Coated; Please specify BS/RAL colour)	13.0kg	18.0kg

### **Installation Parts**

138 120 160	Removable (body only)		13.0kg
138 120 161	Removable (Coated Black) (body only)		13.0kg
138 120 162	Removable (Coated; specify BS/RAL colour) (body only)		13.0kg

### **Product details**

1000mm above ground  
400mm below ground  
114mm diameter tube  
3mm wall thickness

### **Installation & use**

Removable bollards require an excavated hole of at least 300mm square and 400mm deep for the socket.  
This product is guaranteed for 12 months (if installed and used correctly).

**Tel Sales : 02920 855756 - Fax : 02920 887005 - Email : Enquiries@procterContracts.co.uk**

Procter Contracts - North  
Isabella Road  
Leeds  
LS25 2DY

Procter Contracts - South West  
11 Pantglas Industrial Estate  
Bedwas  
CF83 8XD

Procter Contracts -South East  
Codham Hall  
Brentwood  
CM13 3JT