



The PROCTER RPP

The Removable Parking Post is suitable for areas where occasional access is required. The post is typically locked in place over night and removed during the day. Additional ground sockets are available for storing the post in a convenient location when not in use.

The RPP is available in galvanised and galvanised and coated finish. The post is supplied without a padlock thus allowing the user to specify their own preferred lock (The RSP variant includes a High Security Lock).

The PROCTER RPP is shown in galvanised finish.

Product Range

Order Code	Description	Lift-out Weight	Weight
138 100 601	Galvanised	8.0kg	17.0kg
138 100 602	Galvanised & Coated Yellow	8.0kg	17.0kg
138 100 603	Galvanised & Coated	8.0kg	17.0kg

Accessories & installation parts

138 150 205	Additional Ground Socket
138 100 906	40mm Brass Padlock with 2 Keys (Random Key)
138 100 907	40mm Brass Padlock with 2 Keys (Identical Key)

Product details

914mm above ground.
Socket Dimensions 267mm x 152mm x 160mm (h x w x l).
76mm outside diameter galvanised steel tube body.
Polyurethane cap.

Installation & use

It is recommended that posts are placed no further than 1,200mm apart to ensure no vehicle may pass between.
The ground socket must be concreted into a hole of approximately 300mm cubed.
The flap should be flush with the surrounding ground level when closed.
Suitable provision for drainage should be allowed for drainage from the bottom of the excavated hole.
This product is guaranteed for 12 months (*if installed and used correctly*).

Tel Sales : 02920 855756 - Fax : 02920 887005 - Email : Enquiries@procterContracts.co.uk



The PROCTER RSP

The Removable Security Post is suitable for areas where occasional access is required. The post is typically locked in place over night and removed during the day. Additional ground sockets are available for storing the post in a convenient location when not in use.

The RSP is available in galvanised and galvanised and coated finish. The post is supplied with a High Security Sliding Bolt padlock.

The PROCTER RSP is shown in galvanised and coated yellow finish (Padlock included).

Product Range

Order Code	Description	Lift-out Weight	Weight
138 100 701	Galvanised	8.0kg	17.0kg
138 100 703	Galvanised & Coated Yellow	8.0kg	17.0kg

Accessories & installation parts

138 150 205 Additional Ground Socket

Product details

914mm above ground.
Socket Dimensions 267mm x 152mm x 160mm (h x w x l).
76mm outside diameter galvanised steel tube body.
Polyurethane cap.

Installation & use

It is recommended that posts are placed no further than 1,200mm apart to ensure no vehicle may pass between.
The ground socket must be concreted into a hole of approximately 300mm cubed.
The flap should be flush with the surrounding ground level when closed.
Suitable provision for should be allowed for drainage from the bottom of the excavated hole.
This product is guaranteed for 12 months (*if installed and used correctly*).

Tel Sales : 02920 855756 - Fax : 02920 887005 - Email : Enquiries@procterContracts.co.uk



The PROCTER Ground Lock Removable Post

The Ground Lock Removable Post offers a highly effective and robust way to protect premises and vehicles. The Ground Lock Removable Post is supplied with a shallow fitting ground socket from which the post can be removed and placed to one side when not in use. This solution is ideal where the ground prevents the use of Retractable posts. The post is lockable by placing the post in the socket, rotating the post 45° and then pressing the high-security push button 7-pin lock. The post is unlocked, using the supplied key, rotated and then removed.

*The Ground Lock Removable Post is ideal for protecting vehicle forecourts, commercial premises, car parks and domestic driveways.
The PROCTER RemovaPost-GL is shown in galvanised finish with optional PROCTER Red & White chevron reflective label.*

Product Range

Order Code	Description	Lift-out Weight	Weight
138 100 751	RemovaPost-GL (Galvanised)	10.0kg	19.0kg

Accessories & installation parts

138 501 420	Additional Ground Socket
138 811 290	Spare key (please specify key number/product)
138 810 598	PROCTER Red & White Chevron Reflective Label

Product details

745mm above ground.
313mm socket depth.
90mm outside diameter galvanised steel tube body.

Installation & use

It is recommended that posts are placed no further than 1,200mm apart to ensure no vehicle may pass between.
The ground socket must be concreted into a hole of approximately 350mm cubed.
The flap should be flush with the surrounding ground level when closed.
Suitable provision for should be allowed for drainage from the bottom of the excavated hole.
This product is guaranteed for 12 months (*if installed and used correctly*).

Tel Sales : 02920 855756 - Fax : 02920 887005 - Email : Enquiries@procterContracts.co.uk



The PROCTER Removable Post-TLT

The Removable Post-TLT offers a highly effective and robust way to protect premises and vehicles. Supplied with a shallow fitting ground socket, the Removable Post-TLT can be removed and placed to one side when not in use. This solution is ideal for sites where the ground prevents the use of Retractable posts.

The post locks by placing the post in the socket, rotating the post 45° and then pressing the high-security push button 7-pin lock fitted in the top of the post. The post can only be unlocked, rotated and removed using the supplied key.

This post is ideal for protecting vehicle forecourts, commercial premises, car parks and domestic driveways.

Product Range

Order Code	Description	Lift-out Weight	Weight
138 100 791	Removable Post-TLT (Galvanised)	10.0kg	19.0kg

Accessories & installation parts

138 810 598	PROCTER Red & White Chevron Reflective Label
-------------	--

Product details

745mm above ground.
313mm socket depth.
90mm outside diameter galvanised steel tube body.

Installation & use

It is recommended that posts are placed no further than 1,200mm apart to ensure no vehicle may pass between.
The ground socket must be concreted into a hole of approximately 350mm cubed.
The flap should be flush with the surrounding ground level when closed.
Suitable provision for should be allowed for drainage from the bottom of the excavated hole.
This product is guaranteed for 12 months (*if installed and used correctly*).

Tel Sales : 02920 855756 - Fax : 02920 887005 - Email : Enquiries@procterContracts.co.uk