



The PROCTER Rubber Bollard

Manufactured from recycled granulated rubber the PROCTER Universal Rubber Bollard is extremely robust. The bollard's flexible design allows it to bend up to 45 degrees upon impact, without deforming, returning to its original position over time.

The Universal Bollard has no sharp edges and will not splinter upon impact, making it safe for pedestrians, cyclists and drivers alike. Its rubber body and flexible nature mean that expensive replacement costs are avoided should it become damaged.

Supplied ragged only, the Universal Rubber Bollard comes with a ground fixing socket for secure installations. A black finish is standard (a granite finish is also available), and reflective tape is available for added visibility.

Product Range

Order Code	Description	Weight
138 122 000	Universal (Black finish)	25.0 kg
138 122 005	Universal (Granite finish)	25.0 kg

Accessories & installation parts

138 100 968	45mm x 500mm Reflective Tape (please specify colour at time of order).
-------------	--

Product details

1000mm above ground
140mm diameter tube
780mm socket height
1780mm overall height

Installation & use

Ragged bollards require a hole of at least 780mm deep for casting into concrete and are supplied with a ground fixing socket to ensure firm ground anchorage. PROCTER recommends that bollards are placed no further than 1,200mm apart to ensure that no vehicle may pass between them. This product is guaranteed for 12 months (if installed and used correctly).

Tel Sales : 02920 855756 - Fax : 02920 887005 - Email : Enquiries@procterContracts.co.uk

Procter Contracts - North
Isabella Road
Leeds
LS25 2DY

Procter Contracts - South West
11 Pantglas Industrial Estate
Bedwas
CF83 8XD

Procter Contracts -South East
Codham Hall
Brentwood
CM13 3JT



The PROCTER Rubber Bollard

Manufactured from recycled granulated rubber the PROCTER Rubber Bollard is highly durable and ideal for identifying pedestrian and vehicle areas in busy environments.

The bollard is splinter-proof with no sharp edges, making it safe for pedestrians, cyclists and drivers alike. Its rubber body will flex on impact, before returning to its original position over time. The flexible nature of the bollard means that expensive replacement costs can be avoided should it become deformed.

Supplied flanged only, and in a black finish as standard (a granite finish is also available), reflective tape is available to increase visibility.

Product Range

Order Code	Description	Weight
138 122 025	Black finish	17.5 kg
138 122 030	Granite finish	17.5 kg

Accessories & installation parts

138 100 968	45mm x 500mm Reflective Tape (please specify colour at time of order).
-------------	--

Product details

740mm above ground
 140mm diameter

Installation & use

Requires bolting to a suitable concrete surface of at least 300mm³ by means of six M10 bolts.

Supplied with a steel flange plate for bolting to the ground.

PROCTER recommends that bollards are placed no further than 1,200mm apart to ensure that no vehicle may pass between them.

This product is guaranteed for 12 months (if installed and used correctly).

Tel Sales : 02920 855756 - Fax : 02920 887005 - Email : Enquiries@procterContracts.co.uk

Procter Contracts - North
 Isabella Road
 Leeds
 LS25 2DY

Procter Contracts - South West
 11 Pantglas Industrial Estate
 Bedwas
 CF83 8XD

Procter Contracts -South East
 Codham Hall
 Brentwood
 CM13 3JT