



**The PROCTER Verge Marker**

*Manufactured from UV resistant plastic, the Verge Marker is highly durable and the lightweight body is designed with safety in mind. The verge marker flexes up to 90 degrees, returning to its upright position, and will not splinter in the event of an impact.*

*Twin reflective plates make it extremely visible, even in poor weather conditions, or at night. These verge markers are supplied coated in black and white, with a below surface spike for soft ground fixing, or a socket for hard ground fixing.*

**Product Range**

Order Code	Description	Weight
138 107 205	Verge Marker	1.1kg

**Product details**

- 1000mm above ground.
- 405mm below ground (with spike).
- 350mm below ground (with socket).
- 104mm width.
- 5mm thick.
- Two reflective plates; one white, one red.

**Installation & use**

Fixed to ground using a below surface spike for soft ground installation.  
 Fixed to ground using a below surface socket for hard ground installation & require a hole of at least 350mm cubed.  
 Suitable for installation in concrete, asphalt or soil.  
 Concrete cast verge markers require a hole of at least 350mm cubed.  
 This product is guaranteed for 12 months (if installed and used correctly).

**Tel Sales : 02920 855756 - Fax : 02920 887005 - Email : [Enquiries@procterContracts.co.uk](mailto:Enquiries@procterContracts.co.uk)**



**The PROCTER Verge Marker**

*Manufactured from hollow UV resistant plastic, the Fleximarker Verge Marker is highly durable. The lightweight body is designed with safety in mind, flexing up to 90 degrees, and in the event of an impact.*

*Twin reflective plates make it extremely visible, even in poor weather conditions, or at night. These verge markers are supplied coated in black and white, and with a below surface base extension for ground fixing.*

**Product Range**

Order Code	Description	Weight
138 107 200	Verge Marker	1.8kg

**Product details**

1000mm above ground.  
 300mm below ground.  
 127mm diameter.  
 Two reflective plates; one white, one red.

**Installation & use**

Fixed to ground using a below surface base extension.  
 Suitable for installation in concrete, asphalt or soil.  
 Concrete cast verge markers require a hole of at least 300mm cubed.  
 This product is guaranteed for 12 months (if installed and used correctly).

**Tel Sales : 02920 855756 - Fax : 02920 887005 - Email : [Enquiries@procterContracts.co.uk](mailto:Enquiries@procterContracts.co.uk)**

Procter Contracts - North  
 Isabella Road  
 Leeds  
 LS25 2DY

Procter Contracts - South West  
 11 Pantglas Industrial Estate  
 Bedwas  
 CF83 8XD

Procter Contracts -South East  
 Codham Hall  
 Brentwood  
 CM13 3JT